BOROUGH OF SURF CITY, COUNTY OF OCEAN, NJ

813 Long Beach Boulevard, 08008 Telephone (609)494-3064

Email Frontdesk@surfcitynj.org

Rental Application & Certification in Lieu of Inspection

C	•	Fees: × \$4	1		* \$90.00
Dwelling Location	Block	Lot	First day of Ren	tal	
Surf	City Rental Str	eet Address			
*NOTE: ALL BOXE	S MUST BE C	HECKED IN (ORDER FOR THE	CERTIFIC	CATION TO BE VALID
 Smoke detector on each le Smoke detector and carbo All smoke detectors are in All Carbon monoxide alar Fire extinguisher is the co 	on monoxide al working order m(s) are in wo	arm outside ead r rking order	ch separate sleeping	area; and	within 10 feet of bedrooms
Th	nis is ast	ory dwelling [] with [] withou	ıt a basem	ent
	Si	ngle Family: [] Duplex: []		
constructed after January 1977, sha et seq). See diagram on back of this a Mailing address	application for fur	ther information	_	-	
Phone Number	Phone Number		Email Address		
Contact person		Phone Number_			
I would request my cer	rtificate be: (ple	ease choose one) emailed	faxed	in-person pick up
			e by me are true. I an lly false, I will be sub		at if any of the foregoing nalty.
Applicant Name		Notar Sworn to and subscribday of			Notary Seal:
Applicant Signatur	e		Signature		
Once issu	ied, a Certif	icate is not t	ransferrable, nor	is a fee	refundable.
Date Received		FOR O	FFICE USE ONLY		
Check Number	Certification	NT 1	T _o	suing Ager	.

Effective January 1, 2019, the following requirement regarding battery-operated smoke alarms will be enforced under the new NJ Uniform Fire Code Requirements.

N.J.A.C. 5:70-4.19 Smoke alarms for one- and two-family dwellings; carbon monoxide alarms; and portable fire extinguishers:

SMOKE ALARM REQUIREMENTS:

- (a) In one- and two-family or attached single family dwellings subject to the requirements of N.J.A.C. 5:70-2.3. smoke alarms shall be installed as follows:
- 1. On each level of the premises; and
- **2.** Outside of each separate sleeping area.
- (b) The smoke alarms required in (a) above shall be located and maintained in accordance with NFPA 72.
- 1. The alarms shall not be required to be interconnected.
- (c) 10-YEAR SEALED BATTERY-POWERED SINGLE STATION SMOKE ALARMS shall be installed and shall be listed in accordance with ANSI/UL 217, incorporated herein by reference. However, A/C-powered single or multiple-station smoke alarms installed as part of the original construction or rehabilitation project shall not be replaced with battery-powered smoke alarms. The effective date of this subsection shall be January 1, 2019.
- **1.** A/C-powered smoke alarms shall be accepted as meeting the requirements of this section.

CARBON MONOXIDE ALARM REQUIREMENTS:

Carbon monoxide alarms shall be installed in all dwelling units in buildings in one- and two-family or attached single family dwellings, except for units in buildings that do not contain a fuel-burning device or have an attached garage, as follows:

- **1.** Single station carbon monoxide alarms shall be installed and maintained in the immediate vicinity of the sleeping area(s).
- **2.** Carbon monoxide alarms may be battery-operated, hard-wired or of the plug-in type and shall be listed and labeled in accordance with UL-2034 and shall be installed in accordance with the requirements of this section and NFPA-720.

PORTABLE FIRE EXTINGUISHER REQUIREMENTS:

A portable fire extinguisher shall be installed in accordance with the following:

- 1. The extinguisher shall be within 10 feet of the kitchen and located in the path of egress;
- 2. The extinguisher shall be readily accessible and not obstructed from view;
- **3.** The extinguisher shall be mounted using the manufacturer's hanging bracket so the operating instructions are clearly visible;
- **4.** The extinguisher shall be an approved listed and labeled type with a minimum rating of 2A-10B:C and no more than 10 pounds;
- **5.** The owner's manual or written operation instructions shall be provided during the inspection and left for the new occupant;
- **6.** The extinguisher shall be serviced and tagged by a certified Division of Fire Safety contractor within the past 12 months or the seller must have a receipt for a recently purchased extinguisher; and
- 7. The top of the extinguisher shall not be more than five feet above the floor.

To avoid potential false alarms and improper operation, do not install smoke alarms in the following areas:

- ☐ Kitchens Smoke from cooking may cause a nuisance alarm.
- □ Bathrooms Excessive steam from a shower may cause a nuisance alarm.
- ☐ Near heating or air conditioning ducts
- ☐ The "Dead Air" space where the ceiling meets the wall (see Figure 5).
- ☐ The peak of an "A" frame ceiling at the top may prevent smoke from reaching the detector.

